

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

Herrick Technology Laboratories, Inc.

Price List



Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

Contents

HTLx Core Module; HTLx-U	4
HTLx-T2	7
DF1/DF2	9
HPACK	11
DR-4	13
HTLw	15
HTLv-2	19
PNTRv	21
HTLv-C	23

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

General Information

Pricing and Orders:

Pricing provided in this document is “Most Favored Customer or U.S. Government” pricing. Additional discounts may be available for quantities greater than those listed. While every effort has been made to ensure the accuracy of this document, HTL reserves the right to change pricing, specifications, options and accessories without notice. Please contact your HTL representative or Marketing@herricktechlabs.com for a quotation and the latest technical data.

Delivery:

FOB Origin. Delivery of the products contained in this document is typically accomplished within 120 to 180 days after receipt and acceptance of an order. HTL recognizes that schedule requirements vary and in many cases is able to accommodate. Purchase of the optional SAASM GPS requires proof of having COMSEC/STARS account and demonstrable ability to handle SAASM devices at the time of delivery. Please contact your HTL representative or Marketing@herricktechlabs.com with your requirements.

Payment Terms:

As a small business HTL requests performance-based payments per FAR-32-104(b)(c)(d). Payment schedules will be negotiated prior to award.

Warranty:

HTL warrants products to be free from defects in materials and workmanship for a period of two (2) years from the date of shipment.

Export:

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

Contact:

Herrick Technology Laboratories, Inc.
20201 Century Blvd.
Suite 200
Germantown, MD 20874
Phone: (301) 972-2037
Fax: (301) 972-1299
Marketing@herricktechlabs.com

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

HTLx Core Module; HTLx-U

Miniature Quad Transceiver



HTLx Core Module
Shown with Apple iPhone 6



HTLx with Universal Enclosure (HTLx-U)

DESCRIPTION

Small Form-Factor Multichannel HF/VHF/UHF/Microwave Transceiver

The HTLx is a 4 channel Software Defined Radio designed to support various ES and EA missions.

- Extended frequency range 2 MHz-18000 MHz
- 80 MHz IFBW (320 MHz total coverage)
- 80+dB SFDR
- 4 Phase-Coherent or Independently tuned Transceivers (remotely configurable)
- Integrated commercial GPS with INS, optional SAASM, low noise CSAC.
- High performance FPGA including integrated ARM9 cores with NEON coprocessors enable high performance signal processing applications against modern waveforms.
- 2x10GbE Ethernet ports for high speed data transfer.
- Wideband recorder Interface port.
- Optional Removable Media Module (RMM)

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

- Open Architecture including an SDK with Board Support Package to enable rapid development of new capabilities.
- HTLx-U is the HTLx core integrated in the Universal tactical package, which is ideal for rugged mobile applications where IP67 water-immersion resistance is not required.

HTLx

Miniature Quad Transceiver

Model	Part Number / Option Number	Description	Unit Price		
			1 to 5	6 to 15	16 to 25
HTLx Core without SAASM unencrypted	HTLx-101150001	Miniature Quad VHF/UHF/Microwave Transceiver. Core Module without SAASM, Network boot ready	\$93,500.00	\$88,825.00	\$86,955.00
HTLx Core with SAASM unencrypted	HTLx-102150002	Miniature Quad VHF/UHF/Microwave Transceiver. Core Module with SAASM, Network Boot Ready	\$100,000.00	\$95,000.00	\$93,000.00
HTLx Core without SAASM encrypted	HTLx-101100001	Miniature Quad VHF/UHF/Microwave Transceiver. Core Module without SAASM, RMM Ready	\$93,500.00	\$88,825.00	\$86,955.00
HTLx Core with SAASM encrypted	HTLx-102100002	Miniature Quad VHF/UHF/Microwave Transceiver. Core Module with SAASM. RMM ready.	\$100,000.00	\$95,000.00	\$93,000.00
HTLx-U without SAASM	HTLx-U101100003	Miniature Quad VHF/UHF/Microwave Transceiver. Core Module mounted in the Universal Enclosure with RMM and without SAASM	\$110,250.00	\$104,737.50	\$102,532.50

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

HTLx-U with SAASM	HTLx-U102100004	Miniature Quad VHF/UHF/Microwave Transceiver. Core Module mounted in the Universal Enclosure with RMM and with SAASM	\$116,750.00	\$110,912.50	\$108,577.50
HTLx-U/RMM	911-00048-001	Removable Media Module for HTLx-U	\$2,100.00	\$2,100.00	\$2,100.00

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

HTLx-T2

Miniature Quad Transceiver



HTLx-T2

DESCRIPTION

Small Form-Factor Multichannel VHF/UHF Transceiver

The HTLx-T2 is a 4 channel Software Defined Radio designed to support various ES and EA missions in the tactical environment.

- Extended frequency range 2 MHz-18000 MHz
- 80 MHz IFBW (320 MHz total coverage)
- 80+dB SFDR
- 4 Phase-Coherent or Independently tuned Transceivers (remotely configurable)

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

- Integrated commercial GPS with INS, optional SAASM, low noise CSAC.
- High performance FPGA including integrated ARM9 cores with NEON coprocessors enable high performance signal processing applications against modern waveforms.
- 2x10GbE Ethernet ports for high speed data transfer.
- Wideband recorder Interface port.
- Optional Removable Media Module (RMM)
- Open Architecture including an SDK with Board Support Package to enable rapid development of new capabilities.
- Environmentally rugged electronics enclosure qualified for IP67 water immersion at 1 meter for 30-minute duration

HTLx-T2

Miniature Quad Transceiver

Model	Part Number / Option Number	Description	Unit Price		
			1 to 5	6 to 15	16 to 25
HTLx-T2 without SAASM	HTLx-T2101100005	Tactical Miniature Quad VHF/UHF Transceiver 2 MHz to 18 GHz with RMM without SAASM	\$119,700.00	\$113,715.00	\$111,321.00
HTLx-T2 with SAASM	HTLx-T2102100006	Tactical Miniature Quad VHF/UHF Transceiver 2 MHz to 18 GHz with RMM, with SAASM	\$126,200.00	\$119,890.00	\$117,366.00
HTLx-T2/RMM	911-00048-001	Removable Media Module for HTLx-T2	\$2,100.00	\$2,000.00	\$2,000.00

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

DF1/DF2

Switched 4 Element 20 MHz-6 GHz DF Antenna



DF1

DF1 System Block

DESCRIPTION

Switched 4 Element 20 MHz-6 GHz DF Antenna

- 20 MHz – 6 GHz Coverage
- DF Accuracy < 5 degrees
- 2 Channels: 1 Switched 4 Element + 1 Omni
- Low SWAP
- Supports On-the-Move (OTM), At-the-Halt (ATH), and Fixed-Mount Collection & Geolocation
- Quick-Connect single connector and coupling nut mating

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

DF1/DF2


Switched 4 Element 20 MHz-6 GHz DF Antenna

Model	Part Number / Option Number	Description	Unit Price		
			1 to 5	6 to 15	16 to 25
DF1	911-00002-001	Switched 4 Element 20MHz-6GHz DF Antenna	\$39,950.00	\$37,952.50	\$37,153.50
DF2	910-00230-001	Switched 4 Element 20MHz-6GHz DF Antenna with improved EW protection	\$39,950.00	\$37,952.50	\$37,153.50
Monopod 6'	910-00046-001	Telescopic Monopod, integrated 6' (OAL) radio-DF interface cable (RF, Power, & Control)	\$6,200.00	\$5,890.00	\$5,766.00
Monopod 12'	910-00046-002	Telescopic Monopod, integrated 12' (OAL) radio-DF interface cable (RF, Power, & Control)	\$6,800.00	\$6,460.00	\$6,324.00
Fixed-Mount 6'	910-00225-001	Assy, DF Interface, Fixed-Tube, 1/4-20 Mounting, 6'	\$6,150.00	\$5,842.50	\$5,719.50
Fixed mount 12'	910-00225-002	Assy, DF Interface, Fixed-Tube, 1/4-20 Mounting, 12'	\$6,550.00	\$6,222.50	\$6,091.50
Monopod Mounting	910-00289-001	Assy, Monopod Mounting, Telescopic	\$1,260.00	\$1,197.00	\$1,171.80
Breakout Cable	915-00069-001	Breakout (MIL-CIRC) to SMA Cable Kit to be used with HTLx-U	\$2,583.00	\$2,453.85	\$2,402.19

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

HPACK


Quad Transceiver Manpack System



HPACK system Block diagram



HPACK ATH Kit



HPACK OTM Kit

DESCRIPTION

HPACK System: Modular & Expandable system of soldier-worn & portable, rugged SIGINT system components which can be configured to meet various manpack system mission requirements.

- Next generation manpack SIGINT Transceiver System is centered around the HTLx-T2 which is based on the HTLx small SWaP-C Software Defined Radio (SDR) wideband transceiver.
- Manpack System is designed to meet the rugged tactical and environmental demand of dismounted and true OTM missions.

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

- Manpack System provides everything needed to perform Collection and Geolocation missions in a single package for standalone operations or as part of distributed a processing system
- Manpack (one man carry) for OTM and ATH operation
- Full SIGINT mission support, including:
 - Detection, Identification, Copy and Dissemination of TAS, TCS and TOS SOI
 - Electronic Support (ES) and capable of Special Purpose Electronic Attack (SPEA)
- Geolocation
 - Single sensor DF, OTM and ATH
 - Contributor to TNG network by acting as JICD 4.2 TDOA/FDOA collector node or by providing complete geo solutions within a network of cooperative sensors
- Primary user interface is Getac T800, rugged Windows tablet
 - Optional Android GOTS open framework ATAK interface
- Interoperable with COTS MANET and GOTS COMMs devices

HPACK

Quad Transceiver Manpack System

Model	Part Number / Option Number	Description	Unit Price		
			1 to 5	6 to 15	16 to 25
H-PackT2	HPACK-102200003-2	HTL Tactical Manpack ESM System	\$194,500.00	\$184,775.00	\$180,885.00

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

DR-4

Small Form-Factor Wideband Recorder



DR-4 Small Form-Factor Wideband Recorder (shown with HTLx-U)

DESCRIPTION

Small Form-Factor Wideband Recorder

The DR-4 is an SSD array which is interoperable with multiple HTL radio transceivers to support a variety of recorder-based ConOps.

- Interoperable with HTLx & HTLw based systems to provide RF record/RF playback capability from 2 MHz to 18 GHz
 - HTLx: Record/playback one to four 80 MHz channels
 - HTLw: Record/playback one 1000 MHz channel
- Recorded data is precision time-stamped

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

- Low SWaP recorder: 2U, 3.47”H x 5.65”W x 9.5”D, 3.4 lbs. (with SSDs), 50W typical
- Four removable COTS 2.5” PCIe NVMe SSDs
- Selectable Recording Bandwidth:
 - HTLx: 80,70, 60, 50, 40, 30, 20, 18, 10, 5 and 1.25 MHz
 - HTLw: 1000, 500, 250, and 100 MHz
- Thunderbolt 3.0 Data Offload

DR-4

Small Form-Factor Wideband Recorder

Model	Part Number / Option Number	Description	Unit Price		
			1 to 5	6 to 15	16 to 25
DR-4	DR4-2000001	Small Form Factor Wideband Recorder Chassis only. Does not include SSD's. Qty 4 SSD's required (see SSD options below).	\$27,500.00	\$26,125.00	\$25,575.00
DR-4/SSD3.84TB	911-00064-001	Lot of 4 SSD's. 3.84 TB Commercial Temp mounted in removable trays.	\$9,980.00	\$9,481.00	\$9,281.40
DR-4/SSD7.6TB	911-00081-001	Lot of 4 SSD's. 7.6 TB Commercial Temp mounted in removable trays.	\$ 15,860.00	\$15,067.00	\$14,749.80

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

HTLw

Miniature Quad Transceiver



HTLw Core Module

Shown with Apple iPhone 6



HTLw with Universal Enclosure (HTLw-U)

DESCRIPTION

Small Form-Factor Multichannel Microwave Transceiver

The HTLw is a 4 channel Software Defined Radio designed to support various missions.

- Extended frequency range 2 MHz-18000 MHz
- 1 GHz instantaneous BW / channel, 4 GHz total.
- 80+dB SFDR
- 4 Phase-Coherent or Independently Tuned Transceivers (remotely configurable). Multi-unit coherency support
- Integrated commercial GPS with INS, optional SAASM, low noise CSAC.
- High performance FPGA including integrated ARM9 cores with NEON coprocessors enable high performance signal processing applications against modern waveforms.
- 2x10GbE Ethernet ports for high speed data transfer.
- Wideband recorder Interface port.
- Optional Removable Media Module (RMM)

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

- Open Architecture including an SDK with Board Support Package to enable rapid development of new capabilities.
- HTLw-U is the HTLw core integrated in the Universal tactical package, which is ideal for rugged mobile applications where IP67 water-immersion resistance is not required.

HTLw

Miniature Quad Transceiver

Model	Part Number / Option Number	Description	Unit Price		
			1 to 5	6 to 15	16 to 25
HTLw without SAASM	HTLw-101100001	Miniature Quad VHF/UHF/Microwave Wideband Transceiver. Core Module. Without SAASM	\$131,650.00	\$125,067.50	\$122,434.50
HTLw with SAASM	HTLw-102100002	Miniature Quad VHF/UHF/Microwave Wideband Transceiver. Core Module. With SAASM	\$138,150.00	\$131,242.50	\$128,479.50
HTLw-U without SAASM	HTLw-U101100003	Miniature Quad VHF/UHF/Microwave Wideband Transceiver mounted in the Universal Enclosure w/ Commercial Front Panel. With RMM. Without SAASM	\$141,900.00	\$134,805.00	\$131,967.00
HTLw-U with SAASM	HTLw-U102100004	Miniature Quad VHF/UHF/Microwave Wideband Transceiver mounted in the Universal Enclosure w/ Commercial Front Panel. With RMM. With SAASM	\$148,400.00	\$140,980.00	\$138,012.00
HTLw-U/RMM	911-00048-001	Removable Media Module for HTLw-U.	\$2,100.00	\$2,100.00	\$2,100.00

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

HTLv-1

3U VPX Quad Transceiver Module



HTLv-1, 3U VPX Quad Transceiver Module

DESCRIPTION

3U OpenVPX Quad Channel HF/VHF/UHF Transceiver Module

The HTLv-1 is a multichannel Software Defined Radio packaged as a 3U REDI/VITA 67.3 conduction-cooled VPX module designed to support various missions.

- Extended Frequency range 2 MHz – 6 GHz
- 80 MHz IFBW (320 MHz total coverage)

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

- 80+dB SFDR
- 4 Phase-Coherent or Independently tuned Transceivers (remotely configurable)
- Pluggable Unit-to-Unit Coherency Via OpenVPX Backplane VITA 67.3
- High performance FPGA including integrated ARM9 cores with NEON coprocessors enable high performance signal processing applications against modern waveforms.
- Processors Linked together through SERDES Transceivers and Hybrid Memory Cube
- Platform enables high performance signal processing applications against modern waveforms.
- Open Architecture including an SDK with Board Support Package to enable rapid development of new capabilities.

HTLv-1

3U VPX Quad Transceiver Module

Model	Part Number / Option Number	Description	Unit Price		
			1 to 5	6 to 15	16 to 25
HTLv-1	910-00074-002	3U VPX Quad Transceiver Module, 2 MHz to 6 GHz	\$46,350.00	\$44,032.50	\$43,105.50

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

HTLv-2

3U VPX Dual Transceiver Module



HTLv-2, 3U VPX Dual Transceiver Module

DESCRIPTION

3U OpenVPX Dual Channel HF/VHF/UHF/Microwave Transceiver Module

The HTLv-2 is a multichannel Software Defined Radio packaged as a 3U REDI/VITA 67.3 conduction-cooled VPX module designed to support various missions.

- Extended Frequency range 2 MHz – 20 GHz
- 80 MHz IFBW (320 MHz total coverage)
- 80+dB SFDR

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

- 2 Phase-Coherent or Independently tuned Transceivers (remotely configurable)
- Pluggable Unit-to-Unit Coherency Via OpenVPX Backplane VITA 67.3
- High performance FPGA including integrated ARM9 cores with NEON coprocessors enable high performance signal processing applications against modern waveforms.
- Processors Linked together through SERDES Transceivers and Hybrid Memory Cube
- Platform enables high performance signal processing applications against modern waveforms.
- Open Architecture including an SDK with Board Support Package to enable rapid development of new capabilities.

HTLv-2

3U VPX Dual Transceiver Module

Model	Part Number / Option Number	Description	Unit Price		
			1 to 5	6 to 15	16 to 25
HTLv-2	910-00075-002	3U VPX Dual Transceiver Module, 2 MHz to 20 GHz	\$48,900.00	\$46,455.00	\$45,477.00

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

PNTRv

3U VPX Reference Module



PNTRv, 3U VPX Reference Module

DESCRIPTION

3U OpenVPX Precision Navigation and Timing Reference Module

The PNTRv design requirements were derived from the Joint Airborne SIGINT Architecture (JASA) specification. The key specifications of interest for the design of the PNTR from the JASA specification follow. It should be noted that JASA defines a Threshold and an Objective set of requirements.

- Provides low noise 100 MHz reference using Low Noise Chip Scale Atomic Clock (LNCSAC)
- Integrated inertial navigation system (INS) with GPS
- Optional SAASM GPS available with RS232 key fill connectivity
- 100 MHz outputs
- Programmable 250 MHz outputs
- Output 1 PPS synchronous to 100MHz
- On board antenna switching to devices
- 1 GbE Control Interface to OpenVPX Backplane

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

PNTRv

3U VPX Reference Module

Model	Part Number / Option Number	Description	Unit Price		
			1 to 5	6 to 15	16 to 25
PNTRv without SAASM	910-00076-001	3U VPX Precision Navigation and Reference Module without SAASM	\$37,500.00	\$35,625.00	\$33,131.25
PNTRv with SAASM	910-00076-002	3U VPX Precision Navigation and Reference Module with SAASM	\$44,000.00	\$41,800.00	\$38,874.00

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

HTLv-C




Front panel view of hybrid High Performance Embedded Compute (HPEC) Chassis

DESCRIPTION

The HTLv-C is a 3U VPX reference chassis, designed per Technical Standard for Sensor Open Systems Architecture (SOSA™) Reference Architecture, Version 1.0, dated September 7, 2017:

- 16-Slot, 3U VPX Chassis
- Designed per Technical Standard for Sensor Open Systems Architecture (SOSA™) Reference Architecture, Version 1.0 , Sep 7, 2017
- Available Precision Navigation, Timing, and Reference Module (HTL PNTRv)
- Available 3U VPX Transceiver Modules:
 - Supports Independent or Phase Coherent Channels
 - 4-Channel; RX / TX; 2 MHz – 6 GHz (HTLv-1)
 - 2-Channel; RX / TX; 2 MHz – 20 GHz (HTLv-2)
- 1/10 GigE Data Interfaces
- 1 GbE Control Interface to OpenVPX Backplane

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.



16 Slot Backplane

Export of the products contained in this document is controlled under the International Traffic In Arms Regulations (ITAR). A U.S. Department of State license is required prior to export.

HTLv-C

3U VPX Chassis

Model	Part Number / Option Number	Description	Unit Price		
			1 to 5	6 to 15	16 to 25
HTLv-C	HTLv-C-19	3U VPX Chassis and Backplane, includes chassis manager and system support module	\$149,500.00	\$142,025.00	\$139,035.00
3UVPX Power Supply 650W	300-00028	Module 3U VPX Power Supply (VITA62) 650W, 48.2 cond Cooled	\$5,900.00	\$5,605.00	\$5,487.00
3UVPX IO SBC	910-00183-001	Module 3U VPX IO SBC, w/XMC	\$43,000.00	\$40,850.00	\$39,990.00
3UVPX Ethernet Switch	300-00025	Module 3U VPX Ethernet Switch, 12 port Victory-Compliant, 48.2	\$36,000.00	\$34,200.00	\$33,480.00
3UPCIE Switch	300-00029	Module 3U,PCIE Switch	\$11,000.00	\$10,450.00	\$10,230.00